

ANTI – SLIP SAFETY TAPES - RECOMMENDED INSTALLATION INSTRUCTION.

Please Read Before Installation

SURFACE PREPARATION

Our Anti – slip Tape can be quickly applied to most surfaces that are clean, dry and smooth. Surfaces must be free of moisture, dust, rust and dirt. Body oils, grease, wax, soap or detergent film for proper adhesion. Loose scale, rust, paint, concrete or dirt must be removed from surfaces by wire brushing, sanding, sandblasting or other means.

CLEANING INSTRUCTION

Commercial Cleaner: Cleaner such as those based on butyl cello solve (with proper ventilation) or non-phosphate alkaline compounds strong enough to emulsify the various contaminants, can be used to clean the mounting surface. Follow the manufacturer's instructions according to type of cleaner used. For soap or grease use Slip-Guard on Guard Degreaser.

Test for clean Surfaces: Put a few drops of water on the cleaned surface. If the water forms droplets or beads up, repeat the cleaning procedure. When the water spreads out and wets the surface easily, the surface is clean enough to apply the Anti-Slip Tape.

IMPORTANT

To ensure a better bond, pass a warm hair dryer down the length of the tape or mat immediately before installing. This will make the contact adhesive more tacky and ensure a stronger bond. This is especially important if the tape is stored in a cool area or in the trunk of a vehicle overnight in cold weather.

INSTALLATIONS

After determining that the surface is clean, smooth and dry, remove the release paper from the underside of the tape, to expose the pressure-sensitive adhesive. Be certain that it is in the proper alignment, use foot pressure, vinyl wallpaper smoother roller or soft rubber mallet to bond the safety tread in place.

Temperature: Be sure substrate is above 50°F 10°C.

Application to wood : New wood should be primed, or painted prior to application of Anti Slip Tape. Loose paint should be removed from old painted surfaces. **Anti-Slip Tape will not bond to wood surfaces treated with Penta, Creosote or other wood preservatives.**

Application To Metal : Best adhesion is obtained when a product is applied to paint or primed surfaces. Loose scale, painted or should be removed prior to painting or priming old new surfaces.

Application To Smooth concrete, Marble Tile, Terrazzo, etc: Clean thoroughly with commercial vacuum cleaner to remove dust and dirt. Clean, if necessary as outlined above.

NOTE: Tape is not recommended for use over rough or broom finished concrete.

Edge Sealer : Use our Edge sealing compound on all exposed edge if the safety treads will be exposed to unusually heavy wear or excessive amount of water, cleaning solutions, oils, grease gasoline, or other solvents.

Ready To Use : The Anti-Slip Tape can be walked on immediately. Maximum bond of the adhesive occurs about 24 hours after installation.

Cleaning process of Installed roll strips

Clean the surface (installed tape stripe using a plain nylon brush and water. We do not recommend acid Non-abrasive material such as resilient or aqua safety do not attract dirt/dust as much as grit material.

CUSTOMER PLEASE NOTE

No warranties expressed or implied are made or be inferred. Sellers and manufacture only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufactures shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of the inability to use the product. Before installing, purchaser shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

